

K-TRAIL

HIGH-QUALITY · TOUGH · DURABLE

PRO SERIES

D610/ D612-RS

MODEL




D612-10-RS shown
Subject to change



GALVANIZED



DUMP



TANDEM

These 6-foot-wide dump trailers are designed for users who need to transport and unload their equipment and other big loads quickly and easily.

	D610-10-PS	D612-10-RS
Interior (length x width x height)	120" x 72" x 20"	147" x 72" x 20"
Total (length x width)	186" x 93"	209" x 93"
Tires / Rims	225-75-R15 (8 ply)	225-75-R15 (8 ply)
Coupler	2 5/16"	2 5/16"
Rear door configuration	Combination barn doors and spreader gate	Combination barn doors and spreader gate
Payload	7,000 lb	7,000 lb
Trailer weight	2,600 lb	3,000 lb
Axles	2 x 5,200 lb	2 x 5,200 lb
Cylinder capacity	7 tons	7 tons
Cylinder stroke	90"	108"



K-TRAIL

K-TRAIL.CA

INFO@K-TRAIL.CA | 877 248-7018

Specifications may change without notice.

PRO SERIES

D610 / D612-RS MODEL

FEATURES

- Bearing-assisted rolling tarp system
- Adjustable coupler
- 4 welded D-rings
- 3 stake pockets on each side
- Standard stabilizer legs (except on D610 model)
- Side plank holders
- 3-stage hydraulic cylinder
- 2" slipper spring suspension
- 7,000 lb drop leg jack



STANDARD TARP PROTECTOR

HARNESS

- Double contact 7-way plug
- LED lights
- Smart battery charger
- Aluminum box with hydraulic pump
- Cold-weather wiring harness



SLIDE-IN RAMPS

CHASSIS

- 2" x 5" x 3/16" tubular chassis
- Tongue: Steel Grade C5 x 6.7 lb/ft
- 1/8" steel unibody design
- Crossmember every 16" c/c
- Welded diamond steel footstep
- Steel diamond plate fenders



STABILIZER LEGS



EXTENSION



COMBINATION BARN DOORS AND SPREADER GATE

ACCESSORIES & OPTIONS

spare tire, slide-in ramps, mesh side extension



K-TRAIL.CA

INFO@K-TRAIL.CA | 877 248-7018

Specifications may change without notice.