

HIGH-QUALITY · TOUGH · DURABLE

D8216 / DGON8216 MODEL





16-foot dump trailers with a capacity of 14,000 or 21,000 lbs. These trailers are perfect for professionnals who need to transport all their equipment and heavy loads.

D8216-14-PS subject to change









SERIES

GALVANIZED

DUMP

TANDEM

TRIDEM GOOSENECK

	D8216-14-PS	D8216-16-PS	D8216-21-PS	DGON82	16-14-PS D	DGON8216-16-PS	DGON8216-21-PS
Interior (length x width x height)	192" x 82" x 27"						
Total (length x width)	20		317" x 102"				
Tires / Rims	235-80-R16 (14 ply)	215-75-R17 (16 ply)	235-80-R16 (14 ply)	235-80-R16 (14 ply)		215-75-R17 (16 ply)	235-80-R16 (14 ply)
Coupler			Gooseneck 2" 5/16				
Rear door configuration	Combo door						
Payload	10,000 lbs	12,600 II	bs. 18,000	lbs. 1	12,800 lbs	s. 13,500 lbs	s. 19,000 lbs.
Trailer weight	4,275 lbs.	4,520 lb	os. 4,520	lbs.	4,575 lbs.	. 4,575 lbs.	5,200 lbs.
Axles	2 x 7,000 lbs.	2 x 8,000 l	bs. 3 x 7,00	0 lbs. 2	2 x 7,000 lbs	s. 2 x 8,000 lbs	. 3 x 7,000 lbs.
Cylinder capacity	12 tons						
Cylinder stroke	144"						
WARRANTY							
		5 YEAF					
	d a	WELDING				WIRING	
							K-TRAIL.C
IK-TRAIL	INFO@K-TRAIL.CA 877 248-701						

specifications may change without notice

PRO SERIES

D8216 / DGON8216 MODEL

FEATURES

- Bearing-assisted rolling tarp system
- Combo door
- Adjustable coupler
- Standard stabilizer legs
- Side plank holders
- 6 welded D-rings
- 3-stage hydraulic cylinder
- 2 sleeper spring suspension
- 1 x 12,000 lbs. drop leg jack on bumper model
- 2 x 12,000 lbs. drop leg jack on gooseneck models

HARNESS

Double contact 7-way plug

- LED lights
- Smart battery charger
- Aluminum toolbox

FRAME

- 3" x 8" x 3/16" tubing frame
- 1/8" steel unibody design
- C3 crossmember every 16" C/C
- Steel diamond plate fenders
- Welded footboard



STANDARD TARP PROTECTOR



EXTENSION

ACCESSORIES & OPTIONS

spare tire, slide-in ramps, mesh side extension





SLIDE-IN RAMPS



STABILIZER LEGS



COMBO DOOR

Printed in Canada

INFO@K-TRAIL.CA | 877 248-7018

specifications may change without notice